

PRODUCT DESCRIPTION:

This is a semi-matte inkjet paper with a unique look and feel of semi-matte offset prints. This specific aspect of the paper makes it popular for day-to-day proofing when simulating standard offset printing processes.

APPLICATION:

- Proofing
- Large format indoor poster printing

PRINTING CONDITIONS:

- ISOcoated_v2_eci.icc
- ISOcoated_v2_300_eci.icc
- CoatedFOGRA39.icc
- ISOuncoated.icc
- ISOuncoatedyellowish.icc
- UncoatedFOGRA29.icc
- ISOwebcoated.icc
- GRACol2006_coatedlv2.icc

STANDARD SIZES*:

Rolls in 30 meter / 98,4 ft:	13"	17"	24"	36"	42"	44"
Part number:	200136	200176	200096	200036	200076	200046
100 sheets:	A4+	A3+				
Part number:	200066	200006				

*Contact us for other sizes and volume deliveries.

PHYSICAL PROPERTIES:

Weight:	185 gsm						
Finish:	Cast-coated paper with a semi-matte finish						
Ink Compatibility:	Dye-, pigment- and ultrachrome ink						
Drying time:	Instant						
Brightness:	89						
Opacity:	>92						
Gloss:	42						
Paper tint:	<table border="1"> <tr> <td>L</td> <td>a</td> <td>b</td> </tr> <tr> <td>94</td> <td>0,85</td> <td>-2,6</td> </tr> </table>	L	a	b	94	0,85	-2,6
L	a	b					
94	0,85	-2,6					
Lamination:	Cold and Hot						
Storage:	Paper should be stored in its original packaging, protecting it from direct sunlight and moisture. Recommended storing temperature is between 18° C and 23° C.						